
INFORMATION REPORT

CENTRAL INTELLIGENCE AGENCY

This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title

x	ARMY X CINCPAC #		X AIR	X F01	AEC		
- I	ARMY	NAVY	T = 1415	l			
							25
			C-O-N-	F-I-D-E-N-1	-I-A-L		1
							7
					PLEASE	ROUTE	~
					ENCLOSURE	ATTAUHED	25X1
	Attachments	are not	classifi	ied when se	parated from th	is report.	$\Box \left(\mathcal{I}_{\mathcal{Y}} \right)$
Γ	5. Mi	lling mac	hine, Moo	del 341.			25X
		ck drill,			J++		- ,
				າວາສ machine, Mó	del 311	2 AUG	1951
		ltivane a eam hamme		r, Model 40	02		1957
	reobte	's dovern	ment, ea	ch describi	ng one of the f	ne wortheast Collowing machine	es: (7)
		m Durbau	AT MIG D	evarement r	אר יווות און פון אור און און און און און און	ne Machine Indust	
	OTTO OTT	ina Natio , East Ci	naı Anım	ıaı bv~Prodı	acts Export Corp	oration, 4 Wango	chia (M)
	a. Chines	e Bristle	es. an il	lustrated t		sh distributed by	2/10 114 2001
		leaf	lets on e	exports from	m Communist Chir	na	9
TE ACQ	SOURC	E EVALUATI	IONS ARE I	DEFINITIVE. A	PRAISAL OF CONTE	NT IS TENTATIVE	25X1
TE OF O. CE &					REFERENCES	٠.	25X1
					REQUIREMENT NO.	RD	
	-				NO. PAGES	1	
SJECT	Chinese Co	ommunist	Exports		DATE DISTR.	/3 May 195	7
	China				REPORT		
UNTRY							






特點

此型蒸汽錘,係單柱式,構造簡單,操作方便。且為雙衝擊行程,錘之衝擊力,除錘頭本身重量外,再加蒸汽壓力故衝擊力很大。

東北人民政府機械互業管理局

型 写 251%



主要規格

1.	落下重量:	400	公斤
2.	活塞最大行程:	690	公厘
3.	汽缸直徑:	305ф	公厘
4.	錘桿直徑:	150∳	公厘
5.	進氣管直徑:	76¢	公厘
6.	排氣管直徑:	89¢	公厘
7.	砧面尺寸:	250×440	
8.	鍾面尺寸:	250 × 180	公厘
9.	錘中心線至柱架最大距離:	-	公厘
10.	砧面至地面高度:	700	
11.	錘身按裝高度:	3,205	
12.	錘座佔地尺寸:	$2,565 \times 1,425$	
13.	錘重 :	8,000	公斤
14.	錘砧重:	6,000	
15.	總重:	14,000	公斤

型 第 **4**02




異日

用途

本機為離心式送風機中能力最高 之一種,普通在 125 粍水柱以內之風 壓時可以用最小的動力,得到最大的 風量,所以在氣流阻力不甚大的情况 下,使用此種送風機排氣或送風最為 經濟而理想,如通風換氣暖房温風冷 房冷風清靜空氣調劑空氣最為適宜。





東州人民四位工業部端號工業前理局


型 **禁 4**02

規 格 麦

馬力KW	風量(公分)	静 「	注軸廻轉 轉/分	傳動方式	翼數	風口位置
74.6	2100	105	375	V型皮帶	60復式	尚上
37.3	1110	100	482	皮 帶	60似式	jót fr
22.3	780	78	570	,,	48	_fd
14.9	444	105	776	,,	60	_ l: l61 kű
7.4	200	100	1000	V型皮帶	60	下面躺
3.7	130	70	1425	,,	64	ी: विं भें।
2.2	90	25	1320	,,	64	jój sij


尺 寸 麦

KW	Λ	В	Н	L	М	К	N	Р	C	W	О	1)	X	E	F	G	Ф	S	R	自軍
74.6	1320	1764	2810	3075	2490	145	1600	700	2260	2360	1820	752	344	348	840	132	1630	148	700	
37.3	900	1245	2030	2126	1656	157	1130	585	1957	1855	1300	462	180	218	600	80	1023	113	490	
22.3	730	920	1530	1760	1560	•	780	630	1336	1416	1000	470	150	214	480	58	675	85	450	
14.9	564	760	1420	1175	990	140	615	400	1026	1210	754	384	115	114	380	[_70_	740	71	325	450
7.4	410	600	1194	968	928		730	440	879	887	514	240	88	64	300	40	500	75	300	. 385
3.7	370	430	750	787	690	97	430			820	460			! 					İ	
2.2	304	388	650	608	400	163	456	234	384	440	388	111		57	190	57	380		}	4.4



当是当族

型 野 421-SB



本機精密度

名		和	}	間	際	聚	
		717.	• •	最大	最 小	最 大	最 小
汽 缸	與	活	塞	0.105	0.025		
汽缸與	ЙÚ	面墊	圏			0.045	0.010
活塞與	ÌÍ	面墊	圈	0.060	0.009		-
前面頭與	車町	格條筒	套	0.100	0.032		

東州人民的位工業部旅航工業前理局


型 集 421-SB

本 機 主 要 之 規 格

形	*		式	S-49乾濕式
重			量	27.2公斤
活	塞		重	1.8公斤
風			管	1/4时
空	氣	管	徑	3/4时
空	氣消	耗	量	2.5—3.5公尺3/分
打	- 軟		數	1.800次/分
使	用	釬	子	7/8时 (六角)

本機使用上之注意


- 1. 風管水管在使用前必須洗滌清潔。
- 2. 每使用48小時後,必須清掃一次內部壓埃。
- 3、潤滑油應用清潔規格品,保持適當
 貯油量。
- 4. 本機適合于豎坑支柱挖眼脚下打小塊開水平坑道,及開幫。
- 5. 本機不宜在傾斜30度以上的向上採礦。




型 号 311

主要規格


1.	工作台面至正刀架距離:	0 1,300	公厘	10.	最大鉋程:	4,200	公厘
2.	侧刀架轴中心線末端地位:				工作台前進速度:	10	米分
	在工作台上	1,125	公厘		工作台後退速度:	18	米 分
	在工作台下	100	公厘	13.	正刀架每鉋程進刀範圍(季	直方向) 6 0.3	公厘
3.	柱架内侧面間之距離:	1,635	公厘		正刀架每錐程進刀範圍(核		公庭
4.	可能最大工作物長度:	4,000	公厘	_	侧面刀架垂直進刀範圍:		公厘
5.	可货最大工作物寬度:	1,600	公厘		皮帶寬度:		公厘
6.	可能最大工作物高度:	1,200	公厘		J 動機:	15 HP 1,450	轉/分
7.	可鲍菔大工作物重量:	10,000	公斤	18.	體積: 7	.300×3,180×3,696	公厘
8.	工作台面:	4,270×1,350	公厘	19.	重量:	22,000	公斤
9.	最小錐程:	200	公厘				





全道輸插床

型 341




東北人民政府互業部

携械互業管理局

型 3 341

主要規格

1.	插頭行程:	254 公厘
2.	插頭至工作台最大距離:	60-670 公厘
3.	工作台直徑:	510 公厘
4.	工作台左右移動最大距離:	350 公厘
5.	工作台前後移動最大距離:	450 公厘
6.	插頭毎往復一次工作台迴轉範團:	10 <u>2</u> 0
7.	插頭每往復一次工作台左右移動範圍:	0.6-3.2 公厘
8.	插頭每往復一次工作台前後移動範團:	0.18-0.36 公厘
9.	插頭變速範圍:	6 種
10.	馬一連:	2 馬力
11.	重 量:	1,710 公斤
12.	體 積:	1500×1000×2000 公厘



Sanitized Copy Approved for Release 2010/05/21: CIA-RDP80T00246A034500120001-5 中國豬鬃 CHINESE BRISTLES

Shanghai No. 17 assortment (black and white)

Composed of one hundred cases of the following sizes and respective percentage of tops:—

Size:	2"	21/4″	$2\frac{1}{2}''$	2¾″	3"	31/4"	31/2"	3¾″	4''
Case:	25	15	12	11	10	8	6	4	3
Tops:	1. A	ll sizes	40%. 2	All si	zes 90	% (with	excepti	ion 2" 70)%).
Size:	41/4	" 4½	″ 4¾′	" 5"	51/4	″ 5½	″ 5¾	" 6"	
Case:	2	11/	11/4	1/2	1/4	1/4	1/8	1/8	
			1001 0			~			

Tops: 1. All sizes 40%. 2. All sizes 90% (with exception 2" 70%).

Shanghai No. 5 assortment (black and white)

Composed of one hundred cases of the following sizes and respective percentage of tops:—

Size:	2"	21/4″	21/2"	23/4″	3′′
Case:	40	25	20	10	5

Tops: 1. All sizes 40%. 2. All sizes 90% (with exception 2" 70%).

1. Bristles of the specified length (within limits of over- and under-size) constitute 40% (with leeway) in each bundle. Bristles measured ¼ inch under the specified size (within limits of over- and under-size and with leeway) 30%, and those measured ½ inch under the specified size constitute all the rest, about 30%.

Leeway of percentage of tops: Lower ranges must not be lower than: 2" 35%

$$2\frac{1}{4}$$
" 36% $2\frac{1}{2}$ " to 6" 37%

Without over size

Limit fo under size: All sizes 4/16"

2. Leeway of percentage of tops: Lower range 2% maximum

Limit of over size: $2\frac{1}{4}$ " to $5\frac{3}{4}$ "....1/16"

 $6'' \dots 3/16''$

Limit of under size: all sizes 4/16"



Chinese Bristles, a byproduct of hog-raising in the vast Chinese countryside, are procuced in great abundance. China began to export bristles as early as 1895, and has so far won a firm footing in the world wide markets.

Bristles exported from China are of top-grade quality. They possess a wide range of stiffness and length and their colours can be classified into four varieties, viz.: black, white, brown and grey. They

are very lustrous in colour and uniform in size, having high resilliency and a power to endure heat, dryness and dampness. They do not break or soften when rubbed violently against iron and steel. As the fibres bear flags at the tip and a natural scaly formation on the stalk, giving a certain degree of asperity, so they are fully capable of absorbing paints and oils and can penetrate into the narrowest chinks and apertures to remove dirt and grease. Therefore Chinese Bristles are the best materials for making various kinds of industrial, household, medical, cleaning and painting brushes.

According to the different usages, buyers may select various colours of assortments, odd lengths and riflings to their satisfaction.

Tientsin, Tsingtao, North-eastern China and Inner-Mongolian short 55 case assortment (black, grey and white)

Composed of fifty-five cases of the following sizes and respective percentage of tops:—

Size:	21/2"	23/4"	3"	31/4"	31/2"	3¾″	4"	41/4"
Case:	12	7	8	7	5	4	3	2
Tops:	70	80	80	80	80	80	80	80
Size:	41/2"	43/4"	5"	51/4"	51/2"	5¾″	6"	
Case:	2	1	1	1	1	0	1	
Tops:	80	80	80	80	80		80*	

Tientsin, Tsingtao, North-eastern China and Inner-Mongolian 26 case assortment (black, grey and white)

Composed of twenty-six cases of the following sizes and respective percentage of tops:—

Size:	21/2"	23/4"	3"	31/4′′	31/2"	33/4″	4′′
Case:	5	4	5	4	5	2	1
Tops	70	80	80	80	80	80	80

Leeway of percentage of tops: Lower range 3% maximum.

Limit of over size: $2\frac{1}{2}$ " to $5\frac{1}{4}$ " 1/16". $5\frac{1}{2}$ " and 6" 3/16".

Limit of under size: All sizes 4/16"

*Tops: 65% for Tsingtao 6"

Chungking No. 27 assortment (black, grey, brown and white)

Composed of one hundred cases of the following sizes and respective percentage of tops:-

Size: 1	Rifling	s 21/4"	21/2"	$2\frac{3}{4}$ "	3"	31/4"	31/2"	$3\frac{3}{4}''$	4''
Case:	25	15	12	11	10	8	6	4	3
Moment		1 ==== 0	0.07	1	1 • .				

Tops: All sizes 90% with exception riflings

Size:	41/4"	41/2"	43/4″	5′′	51/4"	5½″	5¾ ″	6''
Case:	2	11/2	11/4	1/2	1/4	1/4	1/8	1/8

Tops: All sizes 90%.

Chungking No. 4 assortment (black, grey, brown and white)

Composed of one hundred cases of the following sizes and respective percentage of tops:—

Size:	Riflings	21/4"	21/2"	2¾″
Case:	40	25	20	15
Tops:		90	90	90

Leeway of percentage of tops: Lower range 2% maximum.

Limit of over size: $2\frac{1}{4}$ to $5\frac{3}{4}$ " 1/16"

6" 3/16"

Limit of under size: All sizes 4/16"

RIFLINGS (black and white) — Chungking, Hankow, Shanghai and Tsingtao

Bristles measuring under 2 inches is named as RIFLINGS, which has no percentage of tops.


ODD LENGTH

- 2 inches—Tientsin (Tops: 40% and 70%), Tsingtao (Tops: 70%), Chungking (Tops: 90%).
- 21/4 inches—Tientsin (Tops: 40% and 70%), Tsingtao (Tops: 70%) Northeastern (40%)

CHINA NATIONAL ANIMAL BY-PRODUCTS EXPORT CORPORATION

PACKING

Packed in wooden case, secured with iron wires or steel baling hoops, spray with naphthaline inside the case, net weight of each case of Tientsin, Tsingtao, Northeastern China and Inner-Mongolian products is 110 pounds and that of Chungking, Hankow and Shanghai products is 133-1/3 pounds.



Hankow No. 17 assortment (black and white)

Composed of one hundred cases of the following sizes and respective percentage of tops:—

Size:	2"	21/4″	2½″	2¾″	3"	31/4"	3½"	3¾″	4′′
Case:	10	10	10	10	10	10	9	8	6
Tops:	55	60	60	60	70	70	70	70	70
Size:	41/4'	′ 4½″	43/4′	′ 5″	51/4′	5½	′ 5¾	," 6"	
Case:	5	4	3	2	1	1	1/2	1/2	
Tops:	70	70	70	70	70	70	70	70	

Hankow No. 5 assortment (black and white)

Composed of one hundred cases of the following sizes and respective percentage of tops:—

Size:	2"	21/4"	21/2"	23/4″	3′′
Case:	40	20	20	10	10
Tops:	55	60	60	60	70

Leeway of percentage of tops: Lower ranges not lower than the following percentages:

 2"
 50%

 2½"
 56%

 2½", 2¾"
 57%

 3" to 6"
 67%

Limit of over size: 2" to $5\frac{3}{4}$ " 1/16"

6" 3/16"

Limit of under size: All sizes 4/16"

CHINA NATIONAL ANIMAL BY-PRODUCTS EXPORT CORPORATION



Buyers who are interested in Chinese Bristles are requested to contact with:

CHINA NATIONAL ANIMAL BY-PRODUCTS EXPORT CORPORATION

Postal Address: 4, Wangchia Hutung, East City, PEKING CHINA

Cable Address: BYPRODUCTS PEKING